

## Specifications

Power adapter

1)UL/CUL, PSE, GS, BS, CE, CB, FCC

2)21 Years factory

3)2 years warranty

4)Output:12V 2A

85\*44\*67

Model		YGY-122000
Input Characteristics	Input Voltage	90-246V AC
	Input Connecting plug	EU,US,UK,AU,CN plug can be changeable
	Frequency	47-63Hz
	Efficiency	90%
	Input Current	250mA
	Surging Current	25A/220VAC MAX
	Power Factor	PF>0.70(60%-100% Load)
Output Characteristics	Output Voltage	12V DC
	Output Current	2A
	Output Power	24W
	Ripple and Noise	100mVp-p
	Voltage Error	±1%
	Linear Adj.Rate	≤2%
	Load Regulation Rate	≤5%
	Start, Rise Time	40ms
Protection	Overcurrent Protection	
	Overload Protection	
	Short Circuit Protection	
	Overvoltage Protection	
	Temperature Protection	
Environment	Working Environment	-5°C-50°C
	Store Environment	-10°C-85°C 20% - 90% RH (NO Frost)
Insulation	Insulation Strength	3KV
	Insulation Resistance	500VDC>500MΩ
Others	Size(MM)	95*51*32
	Weight(g)	145g
Package	Professional Package(CM)	47*33*33
	Weight/Cartons	15kg
	Neutral Package(MM)	100pcs/Cartons
	OEM Package(color gift box) designed according to your request	
Application	CCTV Surveillance System,Network Surveillance Camera,DVR,Alarm System,LED,Digital and Electronic Products,and so on.	
Certificate	UL/CUL, PSE, GS, BS, CE, CB, FCC	
	Full 2 years Warranty	